Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking - 1.1 Product identifier - Trade name: PANTAQUICK SCA 28 AFL - Article number: 0528 - 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. - Application of the substance / the mixture Construction chemicals - 1.3 Details of the supplier of the safety data sheet - Manufacturer/Supplier: Ha-Be Betonchemie GmbH Stuevestrasse 39 31785 HAMELN, GERMANY - Further information obtainable from: info@ha-be.com - 1.4 Emergency telephone number: 0049 5151 587-0 Only available during office hours. **SECTION 2: Hazards identification** - 2.1 Classification of the substance or mixture - Classification according to Regulation (EC) No 1272/2008 corrosion Met. Corr.1 H290 May be corrosive to metals. Eve Dam. 1 H318 Causes serious eve damage. - 2.2 Label elements - Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. - Hazard pictograms GHS05 - Signal word Danger - Hazard-determining components of labelling: aluminium sulphate - Hazard statements H290 May be corrosive to metals. H318 Causes serious eye damage. - Precautionary statements P234 Keep only in original packaging. Wear eye protection / face protection. P280 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P390 Absorb spillage to prevent material damage. P406 Store in a corrosion resistant container / container with a resistant inner liner. - 2.3 Other hazards - Results of PBT and vPvB assessment - PBT: Not applicable. (Contd. on page 2) - GB

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

## Trade name: PANTAQUICK SCA 28 AFL

- vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### - 3.2 Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

#### - Dangerous components:

CAS: 10043-01-3 EINECS: 233-135-0 Reg.nr.: 01-2119531538-36-xxxx

# aluminium sulphate

🔆 Met. Corr.1, H290; Eye Dam. 1, H318

(Contd. of page 1)

25-50%

## **SECTION 4: First aid measures**

#### - 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints. Take affected persons into fresh air and keep quiet.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

- 6.2 Environmental precautions: Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections No dangerous substances are released.

#### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire - and explosion protection: No special measures required.

(Contd. on page 3)

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

(Contd. of page 2)

## Trade name: PANTAQUICK SCA 28 AFL

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Protect from frost.
- Storage in a collecting room is required.
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- Additional information about design of technical facilities: avoid any kind of dust-generating process
- Ingredients with limit values that require monitoring at the workplace:
- CAS 231-545-4: amorphe silicic acid

AGW: 4 mg/m<sup>3</sup> (general dust limit, inhalable fraction)

10043-01-3 aluminium sulphate

WEL Long-term value: 2 mg/m<sup>3</sup>

- Regulatory information WEL: EH40/2020
- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.
- Respiratory protection:

Wear a particulate respirator according to EN 149 FFP 2S/3S in areas of dust-generating processes. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

(Contd. on page 4)

GB

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

## Trade name: PANTAQUICK SCA 28 AFL

(Contd. of page 3)

- 9.1 Information on basic physical and chemical properties						
- General Information						
- Appearance:	Fluid					
Form: Colour:	Light grey					
- Odour:	Odourless					
- Odour threshold:	Not determined.					
- pH-value at 20 °C:	3					
- Change in condition						
Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : >100 °C					
- Flash point:	Not applicable.					
- Flammability (solid, gas):	Not applicable.					
- Decomposition temperature:	Not determined.					
- Explosive properties:	Product does not present an explosion hazard.					
- Explosion limits:						
Lower:	Not determined.					
Upper:	Not determined.					
- Vapour pressure:	Not determined.					
- Density at 20 °C:	1.43 g/cm³					
- Vapour density	Not determined.					
- Evaporation rate	Not determined.					
- Solubility in / Miscibility with						
water:	Partly miscible.					
- Partition coefficient: n-octanol/water:	Not determined.					
- Viscosity:						
Dynamic:	Not determined.					
Kinematic:	Not determined.					
- 9.2 Other information	No further relevant information available.					

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Possible in traces.

#### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation Finely devided dust may irritate and dehydrate muccous membrane.

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

(Contd. of page 4)

## Trade name: PANTAQUICK SCA 28 AFL

#### - Serious eye damage/irritation

Finely devided dust may irritate and dehydrate muccous membrane.

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity: The inhalation of microsilica cause a minimum risk of a pulmonary fibrosis.
- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity: LC50 (96h) = 2,6 mg/L (Oncorhynchus mykiss) (ECHA)
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation: Packaging may be reused or recycled after cleaning.
- Recommended cleansing agents: Water, if necessary together with cleaning agents.

#### **SECTION 14: Transport information**

-	1	4.	1	U	N	-	Nu	m	b	er	
		_	_		_		-	_	-		_

- ADR, IMDG, IATA
- 14.2 UN proper shipping name
- ADR

- IMDG, IATA

UN3264

3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (aluminium sulphate) Void CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (aluminium sulphate)

- (Contd. on page 6)
  - GB —

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

## Trade name: PANTAQUICK SCA 28 AFL

	(Contd. of page 5)					
<ul> <li>- 14.3 Transport hazard class(es)</li> </ul>						
- ADR, IMDG, IATA						
- Class	8 Corrosive substances.					
- Label	8					
- 14.4 Packing group						
- ADR, IMDG, IATA	III					
- 14.5 Environmental hazards:						
- Marine pollutant:	No					
<ul> <li>- 14.6 Special precautions for user</li> </ul>	Warning: Corrosive substances.					
- Hazard identification number (Kemler code):	80					
- EMS Number:	F-A,S-B					
<ul> <li>Segregation groups</li> </ul>	Acids					
- Stowage Category	A					
- Stowage Code	SW2 Clear of living quarters.					
- Segregation Code	SG36 Stow "separated from" SGG18-alkalis.					
SG49 Stow "separated from" SGG6-cyanides - 14.7 Transport in bulk according to Annex II of						
Marpol and the IBC Code	Not applicable.					
•						
- Transport/Additional information:	Not dangerous according to the above specifications.					
- ADR						
<ul> <li>Limited quantities (LQ)</li> </ul>	5L					
- Excepted quantities (EQ)	Code: E1					
	Maximum net quantity per inner packaging: 30 ml					
	Maximum net quantity per outer packaging: 1000 ml					
- Transport category	3					
- Tunnel restriction code	E					
- IMDG						
<ul> <li>Limited quantities (LQ)</li> </ul>	5L					
- Excepted quantities (EQ)	Code: E1					
	Maximum net quantity per inner packaging: 30 ml					
	Maximum net quantity per outer packaging: 1000 ml					
- UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC,					
	N.O.S. (ALUMINIUM SULPHATE), 8, III					

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The above information describes exclusively the safety requirements of the product(s) and is based on our present-day knowledge. It does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations. Properties of the product are to be found in the respective product leaflet.

(Contd. on page 7)

GB

Printing date 07.01.2022

Version number 1.04

Revision: 07.01.2022

## Trade name: PANTAQUICK SCA 28 AFL

(Contd. of page 6)

GB

- **Relevant phrases** H290 May be corrosive to metals. H318 Causes serious eye damage.
- Abbreviations and acronyms: Met. Corr.1: Corrosive to metals – Category 1 Eye Dam. 1: Serious eye damage/eye irritation – Category 1